

I Data sheet I

I Condensation-Dehumidifier I

AERIAL®

THE DRYING EXPERTS

AD 540

Application & Function

Operation	Condensation principle (heat-pump technology with energy recovery)
Application	Water damage drying, drying buildings, waterworks, storage, basement, garages, archives, etc.
Suitability	heated rooms up to 450 m ³ ** unheated rooms up to 300 m ³ **

Performance

Case made of coated sheet steel in stainless steel finish
Floor standing. Stability by four rubber bumpers. The units are stackable.
Folding handle for comfortable carrying
Blue-Dry®-Technology for particularly energy-saving operation - even at low humidities and temperatures
Fully hermetic rotary compressor
2-speed energy efficient EC-axial fan for speed-drying and silent drying
Maintenance-friendly refrigerant circuit with service connector
Condenser and evaporator made of copper tubes with aluminium fins
On-demand hot gas defrost system
Easy-to-use electronic eDRY: <ul style="list-style-type: none"> • Display: operating hours • On / off switch • Display: current / rated humidity • desired humidity setting is retained even after power disconnection • continuous operation • fan power adjustable in 2 steps
kWh-counter (calibrated acc. MID), currentless reading

Distributor:



Control Technologies FZE
PO Box 122271, SAIF Zone,
Sharjah, UAE.
T: +971 6 5489626 / 050-1537113
E: sales@ctrltechnologies.com

* Acc to DIN EN810

** Experience values for storerooms - Valid June 2017 - Subject to change



Technical data

Dehumidifying capacity / power	30°C / 80% r.h. = 34,0 l/d / 530 W
	27°C / 60% r.h. = 22,0 l/d / 430 W
	20°C / 60% r.h. = 16,6 l/d / 390 W
consumption *	10°C / 70% r.h. = 11,4 l/d / 330 W

Air flow Speed 1/2 = 500 / 620 m³/h

Working range +1°C up to +34°C
35% r.h. up to 95% r.h.

Noise level 51 dB(A)

Voltage 230 V / 50 Hz

Power cord 4,5 m with plug

Protection class IPX4

Refrigerant R407c

Condensate drain Easy to remove, carry and empty water collecting container (7,0 l.).
Unit shutdown when bucket is full.
Connection spigot for hose 12 x 2 mm

Dimensions Height / Width / Depth
578 / 329 / 380 mm

Weight 24 kgs

Optional accessory Condensate drain hose 12 x 2 mm
wall bracket
Pump-Kit

Display eDRY



Version: 2017-06-27